

FlatSafe Tornado Shelters

1200 Industrial Dr
Yukon, Ok 73099

(866) 520-FLAT(3528)

(405)609-1509



Sales Agreement

Date

Name		Planned Installation Date		Contract Price		
Address		Subdivision Name / Map Location		(Out of Oklahoma N/A)		
City	State	Zip Code	County		Subtotal	
Phone: Residence	Work	Other	Gate Code		Installation	
Expiration Date for Sales Agreement Proposal*		Referred By	Other: _____		Additional Charges	
		Phone Book <input type="checkbox"/>	Web Site <input type="checkbox"/>	TV <input type="checkbox"/>	Radio <input type="checkbox"/>	Total
Shelter Size		Garage Size		Down Payment		
4-6per <input type="checkbox"/> 6-8per <input type="checkbox"/> 8-10 person <input type="checkbox"/> 10 person <input type="checkbox"/> Epoxy <input type="checkbox"/> FRP <input type="checkbox"/> HDPE <input type="checkbox"/> Galv <input type="checkbox"/>		1 Car <input type="checkbox"/> 2 Car <input type="checkbox"/> 3 Car <input type="checkbox"/> Other: _____				
<input type="checkbox"/> Delivery Charge** <input type="checkbox"/> Existing Residence <input type="checkbox"/> New Construction		<input type="checkbox"/> Retain Concrete <input type="checkbox"/> No Water <input type="checkbox"/> Pre-Slab		<input type="checkbox"/> Retain Dirt <input type="checkbox"/> No Electricity <input type="checkbox"/> Pre-Frame		
Notes (Homeowner absent / Shelter location / Special arrival time / Etc.)		Payment Method		Credit Card Information MC / Visa / Discover		
		Cash <input type="checkbox"/>		Name as it appears on card		
		Check <input type="checkbox"/>		Expiration Date		
		C.C. <input type="checkbox"/>		Credit Card Number		
FlatSafe specifications Installer will prepare installation area by removing four (4) inches of slab and/or foundation. Installer will excavate sub-grade material. Due to variations in concrete, FlatSafe is not responsible for concrete chipping which may occur with cutting. Homeowner is responsible for any sub-grade obstructions such as plumbing, utility lines, cables, water or any other obstruction. If rock is found, FlatSafe will charge a one time charge of \$250 if hydraulic equipment is required. FlatSafe will not add any additional charges for the first day. If additional days are required, FlatSafe will charge \$600 for each additional day. If larger rental equipment is required, homeowner is responsible for rental charges. FlatSafe is not responsible if post tension cables are cut. It is the homeowners responsibility to check prior to install for post tension cables.						
Customer Information Bulletin Verification I have received a copy of, and will review, the Customer Information Bulletin. _____ Customer's Initials						
*Cancellation In the event Homeowner wishes to cancel shelter installation, after the execution of this agreement but before installation commences, Installer shall retain the down payment. Full sales agreement price is due &/or non-refundable if canceled after installation crew arrival. FlatSafe Tornado Shelters reserves the right to place an expiration date on any proposed sales agreement.						
** Delivery Charge Delivery charges may apply.						
Alterations Due to the wide variation in home construction, some installations may require modification or alteration to ensure proper installation. Any alterations or modifications initiated by Homeowner or Installer must be agreed upon between the parties and the price fixed by them before work on such alteration or modification shall commence. Payment for such alteration or modification shall be made at the time of job completion.						
Building Permits FlatSafe Tornado Shelters Representative shall provide required specifications and structural analysis for securing necessary permits. Unless notified by FlatSafe Representative, homeowner shall be responsible for obtaining required permits. Visit www.flatsafe.com for Specifications & Permit information.						
Warranty The FlatSafe warranty covers structural failure of Galvanized, HDPE and FRP Composite Components on a FlatSafe Tornado Shelter used in domestic dwellings in the United States due to corrosion within 50 years from the date of installation. Date and installation location ("host dwelling") provided by consumer upon registration. Ungalvanized FlatSafe shelters with an Epoxy coating are warranted for 10 years from the date of installation. Visit www.flatsafe.com for entire warranty information.						
Sales Agreement Acceptance This sales agreement, specifications and conditions are acceptable. A FlatSafe Tornado Shelters certified installer is authorized to do work as specified.						
X						
Customer Signature		Date		Sales Rep Signature		